

## MODEL 14 WARNING LIGHT



*Model 14 warning lights feature two sealed-beam incandescent lamps.*

Federal Signal's Model 14 warning light provides reliable lighting even in the toughest conditions.

The Model 14 features two sealed-beam incandescent lamps that create 35,000 candelas of warning light. For attention-getting power, the lighting assembly rotates at 95 flashes per minute. The snap holder over each lamp makes bulb changes quick and easy.

The Model 14 has a polycarbonate base which is impact resistant and can be mounted permanently (model 444112) or temporarily with a magnetic mount (444132). A cigarette lighter plug is included with the magnetic mount version.

A variety of accessories are available for the Model 14: branch guard (447303), vibration mount (447302), and self-leveling bracket (210880).

### QUICK REFERENCE

#### FEATURES

- Dual sealed beam halogen lamps.
- Available with impact-resistant polycarbonate base.
- Durable acrylic dome.
- Exposed materials are non-corrosive for extended service life.
- Rugged construction.

#### APPLICATIONS

- Emergency vehicles
- Utility and construction vehicles

#### REPLACEMENT PARTS

Bulb, 12V	Z8107A033
Motor, 12V	Z8422508A
Dome, red	Z8422C002-01
Dome, blue	Z8422C002-09
Dome, amber	Z8422C002-04
Dome, clear	Z8422C002-05
Dome, green	Z8422C002-06

#### RELATED PRODUCTS

- Model 100 Rotating Light  
Bulletin #4100
- Sentry® Warning Beacon  
Bulletin #4129
- IVP Rotating Beacon  
Bulletin #4128



*A branch guard (left), vibration mount (center), and self-leveling bracket (right) are available for Model 14 warning lights.*

## How To ORDER

1. Specify a model.
  - 444112 14SB with polycarbonate base, permanent mount
  - 444132 14SB with magnetic mount and cigarette lighter plug
2. Specify dome color: red, blue, amber, clear, or green.
3. Order accessories.
  - 447303 Branch guard
  - 447302 Vibration mount kit
  - 210880 Self-leveling bracket

## FACTORY SET SPECIFICATIONS

Model	Input Voltage	Current Draw	Lamp Type	Flash Rate
All	12.8VDC	4.7 amps	30W, Incand.	95/min.

## DIMENSIONS

Model	Height		Width		Depth		Ship. Weight	
	in.	cm.	in.	cm.	in.	cm.	lbs.	kg.
All	8.5	21.6	8.5	21.6	7.5	19.1	4.5	2.0



*An ISO 9001 Certified Supplier*  
**FEDERAL SIGNAL CORPORATION**  
Emergency Products

2645 Federal Signal Drive, University Park, IL 60466-3195  
Tel.: (800) 264-3578 • Fax: (800) 682-8022  
Web: [www.fedsig.com](http://www.fedsig.com)

Sentry is a trademark of  
Federal Signal Corporation.

©2002 Federal Signal Corporation