



462121 (shown with trim ring)

## RENEGADE®

The Renegade® strobe breaks away from the pack and sets new standards for dependability and performance. The Renegade strobe features a rugged, impact-resistant polycarbonate dome and base. The versatile base on model 462121 enables mounting via the permanent base, the trim ring (supplied), or the integrated 1/2-inch pipe mount. Model 462141 utilizes a magnetic mount and comes with a cigarette lighter plug.

For effective long-term operation, the Renegade has a powerful flash tube (replaceable) and vibration-resistant circuit board. The 2.2-joule (double-flash) power supply automatically adjusts to function at any voltage from 12 to 48 VDC. This strobe has exceptional optics and meets SAE J1318 Class 3 specifications. Renegade strobes are designed for reliable performance in the toughest environments. Applications include forklifts, electric vehicles, and industrial trucks and equipment. All models are supplied with an enclosed base and all necessary mounting hardware.

### SPECIFICATIONS

#### Dimensions (Dia. × H.)

462121 2.9 in × 4.4 in  
(73 mm × 110 mm)

462141 2.9 in × 4.4 in  
(73 mm × 110 mm)

Flash Rate: 70±5 (double-flash)  
per minute

Voltage: 12–48VDC

Amp Draw: 0.3 @ 12V

Ship. Weight: 0.9 lbs (0.4 kg)  
approx.

Joules: 2.2 J

Power: 2.6W



### EFFECTIVE

- 2.2-joule (double-flash) strobe power supply produces attention-getting warning
- Versatile base for universal mounting
- Fresnel lens redirects light for maximum visibility

### RELIABLE

- Performs at 12–48VDC
- O-ring gasket seals out moisture
- RFI suppression
- Protected against voltage spikes and reverse polarity

### DURABLE

- Impact-resistant polycarbonate dome and base
- Vibration-resistant circuit board
- Easily replaceable flash tube

### APPLICATIONS

- Forklifts
- Industrial trucks
- Electric vehicles
- Mail carriers

### APPROVALS

- SAE J1318 Class 3



**ORDERING INFORMATION**

**MODELS**

- 462121 Renegade, doubleflash, 12-48VDC, permanent/pipe mount
- 462141 Renegade, double-flash, 12-48VDC, magnetic mount with cord

**OPTIONS**

- 462400 Magnetic mount

**REPLACEMENT PARTS**

- 462500-02 Amber dome
- 462500-03 Blue dome
- 462500-04 Red dome
- 462500-05 Clear dome
- 462500-06 Green dome
- 462500-07 Purple dome
- 462510 Flash tube
- 462520 Trim ring
- 462530 Dome gasket
- 462540 Mounting gasket



462141



462400

