

FIREBALL® COMPACT STROBE



The powerful strobe and compact size of the FireBall® allow it to be used for a wide variety of applications.

Federal Signal's FireBall® strobe light is one of the most compact, high-power strobes available. Although it is less than 5 inches high, it produces an effective flash as powerful as strobes much larger in size. Its size enables the FireBall strobe to be mounted in a wide variety of applications.

DESIGNED FOR DURABILITY

The FireBall strobe has an integral, self-contained power supply. All exposed components are corrosion resistant. The FireBall also features an impact-resistant polycarbonate dome, die cast base, and a stainless steel retaining ring.

These units produce 75 double flashes per minute (11 joules per double flash, 150 total per minute).

FireBall strobes are available in permanent or magnetic mount. Magnetic mount units include a swivel bracket for using the FireBall on sloped surfaces.

WIDE RANGE OF APPLICATIONS

FireBall strobes are ideal for law enforcement, volunteer fire, municipal maintenance, and construction vehicles. The magnetic version is ideal for temporary use, and its compact size makes it easy to store.

QUICK REFERENCE

FEATURES

- Powerful strobe flash in a compact package—perfect for difficult mounting applications.
- Each unit is multi-volt (12/24V).
- Metal base and polycarbonate dome for durability.
- Self-contained power supply.
- Permanent or magnetic mount.

APPLICATIONS

- Volunteer Fire
- Police Applications
- Utility vehicles

REPLACEMENT PARTS

Dome, Clear	Z8550C095A
Dome, Blue	Z8550C095A-01
Dome, Amber	Z8550C095A-02
Dome, Red	Z8550C095A-03
Dome, Green	Z8550C095A-04
Strobe Tube	Z8107146C

RELATED PRODUCTS

UltraStar™ Strobe Beacons
Bulletin #4134

Sentry® Warning Beacons
Bulletin #4129

Model 100 Rotating Light
Bulletin #4100

IVP Rotating Light
Bulletin #4128

FireBeam® / MagnaBeam®
Warning Lights
Bulletin #4122

HOW TO ORDER

1. Specify a model.

Permanent mount:

600611 75 double flashes/minute, 12-24V

Magnetic mount:

(models include 10' cord and cigarette plug and swivel bracket for using FireBall on sloped surfaces)

600641 75 double flashes/minute, 12-24V

2. Specify dome color: amber, blue, red, clear, or green.

SPECIFICATIONS				
Model	Volts	Flash Rate	Current Draw	Joules
600611	12/24	75 double	1.6 amps	11J/double flash
600641	12/24	75 double	1.6 amps	11J/double flash

DIMENSIONS						
Model	Diameter		Height		Ship. Weight	
	in.	cm.	in.	cm.	lbs.	kg.
All	3.9	10.0	4.9	12.5	3.0	1.4